



Picture shown may not reflect actual package.

C15 SOUND ATTENUATED ENCLOSURES

Larne 50 Hz/60 Hz

These sound attenuated, factory installed enclosures incorporate internally mounted super critical level silencers, designed for safety and aesthetic value on integral fuel tank base or optional dual wall integral fuel tank base for total fluid containment. These enclosures are of extremely rugged construction to withstand exposure to the elements and provide weather protection.

FEATURES

ROBUST/HIGHLY CORROSION RESISTANT CONSTRUCTION

- Factory installed on integral fuel tank base
- Environmentally friendly, polyester powder baked paint
- 1.6 mm (0.063 in) galvanized steel
- All round overhanging base to protect enclosure
- High-grade engineering thermoplastic corner posts for protection
- Integral lifting frame
- Compression door latches giving solid door seal
- Zinc plated or black coated stainless steel fasteners
- Internally mounted super critical exhaust silencing system

EXCELLENT ACCESS

- Large cable entry area for installation ease
- Accommodates rear mounted breaker and control panel
- Double doors on both sides
- Vertically hinged doors with solid bar door stays to hold doors open at 135° rotation
- Lube oil and coolant drains pipes to exterior of enclosure and terminated drain valves
- Radiator fill cover

SECURITY AND SAFETY

- Lockable access doors which give full access to control panel and breaker
- Cooling fan and battery charging alternator fully guarded
- Fuel fill, oil fill and battery can only be reached via lockable access
- Externally mounted emergency stop button
- Designed for spreader-bar lifting to ensure safety
- Control panel viewing window
- Stub-up area is rodent proof

OPTIONS

- Cat yellow or white paint
- Integral dual wall fuel tank base for total fluid containment (fuel, oil and coolant)


SOUND ATTENUATED ENCLOSURE OPERATING CHARACTERISTICS

60 Hz SA Enclosure (Low BSFC)			Ambient Capability*		Airflow Rate		Sound Pressure Levels dBA @ Full Load			Exhaust Back Pressure	
ekW	kVA	PP/SB	°C	°F	m³/s	cfm	1 m	7 m	15 m	in/H ₂ O	kPa
500	625.0	SB	45	113	6.3	13,349	83.5	73.3	67.3	16.0	4.1
455	568.8	PP	43	109	6.3	13,349	82.9	72.7	66.7	14.3	3.6
450	562.5	SB	49	120	6.3	13,349	82.9	72.6	66.6	14.1	3.5
410	512.5	PP	48	118	6.3	13,349	82.4	72.1	66.1	12.5	3.1
400	500.0	SB	54	129	6.3	13,349	82.3	72.0	66.0	12.2	3.0
365	456.3	PP	52	126	6.3	13,349	82.0	71.6	65.6	10.9	2.7

*Ambient measured with Cat Extended Life Coolant

50 Hz SA Enclosure (Low BSFC)			Ambient Capability*		Airflow Rate		Sound Pressure Levels dBA @ Full Load			Exhaust Back Pressure	
ekW	kVA	PP/SB	°C	°F	m³/s	cfm	1 m	7 m	15 m	in/H ₂ O	kPa
440	550	SB	41	106	5.7	12,078	80.7	70.6	64.6	10.8	2.7
400	500	PP	40	104	5.7	12,078	80.3	70.2	64.2	9.6	2.4
400	500	SB	46	115	5.7	12,078	80.3	70.2	64.2	9.6	2.4
364	455	PP	45	113	5.7	12,078	80.0	69.9	63.9	8.0	2.0
360	450	SB	51	124	5.7	12,078	80.0	69.9	63.9	7.9	2.0
328	410	PP	51	124	5.7	12,078	79.7	69.6	63.6	6.5	1.6

*Ambient measured with Cat Extended Life Coolant



Approximate weight of enclosure package: 5280 kg (11,640 lb). Exact weight is dependent on options. Enclosure weight includes: sound attenuated enclosure, exhaust system, base and generator set. Generator set enclosure also available in white. (Cat yellow is standard color)

Information contained in this publication may be considered confidential.

Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

www.Cat-ElectricPower.com

© 2011 Caterpillar
All Rights Reserved.
Printed in U.S.A.